


PCM-3614I/3618I

PCM-3641I

4/8-port RS-232/422/485
PCI-104 Module

4-port RS-232 PCI-104
Module



PCM-3614I



Features

- Automatic RS-485 data flow control
- Shared IRQ settings for each port
- LED indicators: TX, RX
- Standard PC ports: COM1, COM2, COM3, COM4 compatible
- Supports Windows 2000/XP/Vista/7 and Linux
- Supports WinCE 5.0/6.0
- Powerful and easy-to-use utility (ICOM Tools)

Specifications

General

- Card Interface** PCI-104
- Connectors** PCM-3614I: 1 x 40-pin box header
PCM-3618I: 2 x 40-pin box header
- Ports** PCM-3614I: 4
PCM-3618I: 8
- Power Consumption** +5V @ 450 mA

Communications


- Data Bits** 5, 6, 7, 8
- Data Signals** RS-422: TxD+, TxD-, RxD+, RxD-, CTS+, CTS-, RTS+, RTS-
RS-485: DATA+, DATA-, GND
RS-232: TxD, RxD, RTS, CTS, DTR, DSR, DCD, RI, GND
- IRQ** 3, 4, 5, 6, 7, 9, 10, 11, 12, 15
- Parity** None, Even and Odd
- Speed** 50 bps ~ 921.6 kbps
- Stop Bits** 1, 1.5, 2
- Termination Resistor** 120 Ω

Environment

- Operating Humidity** 0 ~ 90 % RH
- Operating Temperature** -40 ~ 85°C (-40 ~ 185°F)
- Storage Temperature** -40 ~ 85°C (-40 ~ 185°F)

Ordering Information

- PCM-3614I** 4-port RS-232/422/485 PCI-104 Module
- PCM-3618I** 8-port RS-232/422/485 PCI-104 Module



PCM-3641I



Features

- Transmission speeds up to 460 kbps
- Shared IRQ settings for each port
- Standard PC ports: COM1, COM2, COM3, COM4 compatible
- Supports Windows 2000/XP/Vista/7 and Linux
- Supports WinCE 5.0/6.0
- Powerful and easy-to-use utility (ICOM Tools)

Specifications

General

- Card Interface** PCI-104
- Connectors** 1 x 40-pin box header
- Ports** 4
- Power Consumption** +5V @ 250 mA (max.)

Communications

- Data Bits** 5, 6, 7, 8
- Data Signals** TxD, RxD, RTS, CTS, DTR, DSR, DCD, RI, GND
- IRQ** 3, 4, 5, 6, 7, 9, 10, 11, 12, 15
- Parity** None, Even and Odd
- Speed** 50 bps ~ 460.3 kbps
- Stop Bits** 1, 1.5, 2
- Termination Resistor** 120 Ω

Environment

- Operating Humidity** 0 ~ 90 % RH
- Operating Temperature** -40 ~ 85°C (-40 ~ 185°F)
- Storage Temperature** -40 ~ 85°C (-40 ~ 185°F)

Ordering Information

- PCM-3641I** 4-port RS-232 PCI-104 Module